TCG ACPI Specification

Family "1.2" and "2.0"

Version 1.2, Revision 8

February 27, 2017

Committee Draft

Contact: admin@trustedcomputinggroup.org

• Work in Progress: This document is an intermediate draft for comment only and is subject to change without notice. Readers should not design products based on this document.

TCG Public Review

Copyright © TCG 2017

TCG

Disclaimers, Notices, and License Terms

THIS SPECIFICATION IS PROVIDED "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NONINFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.

Without limitation, TCG disclaims all liability, including liability for infringement of any proprietary rights, relating to use of information in this specification and to the implementation of this specification, and TCG disclaims all liability for cost of procurement of substitute goods or services, lost profits, loss of use, loss of data or any incidental, consequential, direct, indirect, or special damages, whether under contract, tort, warranty or otherwise, arising in any way out of use or reliance upon this specification or any information herein.

This document is copyrighted by Trusted Computing Group (TCG), and no license, express or implied, is granted herein other than as follows: You may not copy or reproduce the document or distribute it to others without written permission from TCG, except that you may freely do so for the purposes of (a) examining or implementing TCG specifications or (b) developing, testing, or promoting information technology standards and best practices, so long as you distribute the document with these disclaimers, notices, and license terms.

Contact the Trusted Computing Group at <u>www.trustedcomputinggroup.org</u> for information on specification licensing through membership agreements.

Any marks and brands contained herein are the property of their respective

Change History

Revision	Description				
1	Copy of TCG ACPI Specification 1.10 add support for TCG log in TPM2 ACPI table				
2	Add Qualcomm proposal for SMC start method				
3	Added note that log format is defined in PC Client PFP specification for TPM 2.0				
4	Clarified note about log format for TPM 2.0, updated footer and header				
5	Clarified language on crypto agile log format.				
6	Incorporate feedback from Technical Committee				
7	Formatting feedback from workgroup				
8	Incorporate feedback from Technical Committee				

Contents

Ch	ange H	istoryii	i					
Сс	ontents	ἰν	/					
Lis	t of Tab	les	/					
1	Scope	9	I					
2	Introd	uction1	1					
3	Terms	s and definitions	2					
4	Abbre	viations	3					
5	Comp	liance	1					
6	Conve	entions	1					
	6.1	Bit and Octet Numbering and Order	1					
	6.2	Numbers	1					
7	ACPI	Table	3					
	7.1	Client ACPI Table for TPM 1.26	3					
	7.1.1	Client Common Header Values6	3					
	7.1.2	ACPI Table Layout	3					
	7.2	Server ACPI Table for TPM 1.2	7					
	7.2.1	Server Common Header Values7	7					
	7.2.2	ACPI Table Layout7	7					
	7.2.3	Device Flags)					
	7.2.4	Interrupt Flags	3					
	7.3	ACPI Table for TPM 2.0)					
	7.3.1	7.3.1 Start Method Specific Parameters for ARM SMC Start Method (11)						
8	ACPI	Device	3					
;	8.1	.1 Optional Start Method for TPM 2.0 devices						

List of Tables

Table 1: Defined values for Client ACPI Table for TPM 1.2	6
Table 2: TCG Hardware Interface Description Table Format for TPM 1.2 Clients	6
Table 3: Defined values for Server ACPI table for TPM 1.2	7
Table 4: TCG Hardware Interface Description Table Format for TPM 1.2 Servers	7
Table 5: Bit layout of Device Flags	9
Table 6: Bit layout of Interrupt Flags	9
Table 7: TCG Hardware Interface Description Table Format for TPM 2.0	10
Table 8: Start Method values for ACPI table for TPM 2.0	11
Table 9: Start Method Specific Parameters for ARM SMC	11
Table 10: TCG Hardware Device Object Control Methods	14

1 Scope

This specification defines the framework of necessary ACPI tables and basic methods to be used on a TCG compliant platform. The table and ACPI namespace objects provide enough information to the operating system to enable access to the TCG compliant hardware in a platform.

2 Introduction

The intention of this specification is to provide a framework for all platform types that employ ACPI. These platform types can draw from this specification as necessary, and may further specify ACPI functionality that is required for a particular platform type.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

buffer

data structure used for transport to and from the TPM

3.2 CLEAR

bit with a value of zero (0), or the action of causing a bit to have a value of zero (0)

3.3 command

the values sent to the TPM to indicate the operation to be performed

3.4

octet

eight bits of data

Note: On most modern computers, this is the smallest addressable unit of data.

3.5

response

values returned by the TPM when it completes processing of a command

3.6 SET

bit with a value of one (1), or the action of causing a bit to have a value of one (1)

3.7 TPM Device Reset

resetting of TPM internal state due to _TPM_Init

3.8 Trusted Platform Module TPM

implementation compliant with the TPM Main Specification; Family 1.2 or TPM Library Specification; Family 2.0; Level 00; Revision 116 or later.

4 Abbreviations

For the purposes of this document, the following abbreviations apply.

Abbreviation	Description
_CID	Compatibility ID
_HID	Hardware ID
TPM	Prefix for an indication passed from the system interface of the TPM to a Protected Capability defined in a TPM specification
ACPI	Advanced Configuration and Power Interface ([ACPI 5.0] refers to version 5.0 of the ACPI specification at http://uefi.org/acpi/specs)
ASL	ACPI Source Language
APIC	Advanced Programmable Interrupt Controller
CPU	Central Processing Unit
DSDT	Differentiated System Description Table
DWORD	Double word, a 32-bit number
FADT	Fixed ACPI Description Table (See [ACPI 5.0] for the definition)
GAS	Generic Address Structure (See [ACPI 5.0] for the definition)
GPE	ACPI General Purpose Event register block (See [ACPI 5.0] for definition)
GPEx_STS	ACPI GPE Status register (part of the GPE register block specific for the event denoted by 'x' (0 or 1)
GSIV	Global System Interrupt Vector
ID	Identifier
I/O	Input/Output
LAML	Log Area Minimum Length
LASA	Log Area Start Address
MMIO	Memory Mapped IO
MSO	Most Significant Octet
NO-OP	No operation. A CPU operation that does nothing.
OEM	Original Equipment Manufacturer
OS	Operating System
OSPM	Operating System Power Management
PCI	Peripheral Component Interconnect
PNP	Plug and Play
SAPIC	Streamlined APIC
SCI	System Control Interrupt
TCG	Trusted Computing Group
TPM	Trusted Platform Module
TPM2_	Prefix for a command defined in the TPM 2.0 Library specification
QWORD	Quad Word, a 64-bit number
WORD	Word, a 16-bit number

5 Compliance

Systems providing an ACPI table for TPM 1.2 or TPM 2.0 have to adhere to the layout of the tables described in this specification. A TCG compliant platform that implements ACPI SHALL provide the ACPI tables appropriate for the platform type.

6 Conventions

Text in this specification on a white background is normative. Informative text is formatted with a grey background.

6.1 Bit and Octet Numbering and Order

An integer value is considered to be an array of one or more octets. The octet at offset zero within the array is the most significant octet (MSO) of the integer. Bit number 0 of that integer is its least significant bit in the last octet in the array.

Example: A 32-bit integer is an array of four octets; the MSO is at offset [0], and the most significant bit is bit number 31. Bit zero of this 32-bit integer is the least significant bit in the octet at offset [3] in the array.

Note: Array indexing is zero-based.

Note: This definition does not match the "network bit order" used in many IETF documents, such as RFC 4034. In those documents, the most significant bit of a datum has the lowest bit number. It is conventional practice to send that bit first when using a serial network protocol, and the bits are numbered in the order in which they are sent. This specification numbers bits according to the power of two to which they correspond within a datum. This numbering corresponds to the normal convention for bit numbering in hardware registers that hold integer values rather than fixed-point numbers.

The first listed member of a structure is at the lowest offset within the structure and the last listed member is at the highest offset within the structure.

For a character string (letters delimited by ""), the first character of the string contains the MSO.

6.2 Numbers

Numbers are decimal unless a different radix is indicated.

Unless the number appears in a table intended to be machine readable, the radix is a subscript following the digits of the number. Only radix values of 2 and 16 are used in this specification.

Radix 16 (hexadecimal) numbers have a space separator between groups of two hexadecimal digits.

Example: 40 FF 12 34₁₆

Radix 2 (binary) numbers use a space separator between groups of four binary digits.

Example: 0100 1110 0001₂

For numbers using a binary radix, the number of digits indicates the number of bits in the representation.

Example: 20_{16} is a hexadecimal number that contains exactly 8 bits and has a decimal value of 32.

Example:	$10\ 0000_2$ is a	binary	number	that	contains	exactly	6 ł	oits	and	has	а
	decimal value	of 32.									

Example: $0\ 20_{16}$ is a hexadecimal number that contains exactly 12 bits and has a decimal value of 32.

A number in a machine-readable table may use the "0x" prefix to denote a base 16 number. In this format, the number of digits is not always indicative of the number of bits in the representation.

Example: 0x20 is a hexadecimal number with a value of 32, and the number of bits is determined by the context.

7 ACPI Table

All TCG platforms supporting ACPI utilize the same header section layout, which is separated from the rest of the table with a double line. Table 2 describes the client ACPI table for TPM 1.2. Table 4 describes the server ACPI table for TPM 1.2. Table 7 describes the ACPI table for TPM 2.0, which can be used for client or server platforms.

The value in the signature field for the TPM 2.0 table (TPM2') differs from the value for the TPM 1.2 tables (TCPA').

ACPI tables have the little-endian byte format defined in the ACPI specification.

7.1 Client ACPI Table for TPM 1.2

7.1.1 Client Common Header Values

These are the specific values to be used in the client platform version of the ACPI table for TPM 1.2.

Field	Value	Description
Length	50	Size of the table
Revision	2	Revision for PC Client Platform Class
Platform Class	0	PC Client Platform Class

Table 1: Defined values for Client ACPI Table for TPM 1.2

7.1.2 ACPI Table Layout

Table 2: TCG	Hardware Ir	nterface Des	scription Table	Format for	TPM 1.2 Clients

Field	Byte Length	Byte Offset	Description
Header			
Signature	4	0	'TCPA'. Signature for the TCG Hardware Interface Table.
Length	4	4	See section 7.1.1. The length of this table starting from the Signature field up to and including the LASA field. It does not include the size of the area storing events or other data that is referenced or pointed to by any of these fields.
Revision	1	8	See section 7.1.1. Revision of this table including the data and structures referenced by it. E.g., if the event structures with the area referenced by LASA change, this revision shall be incremented.
			Note: The purview of this revision is within platform class as indicated by the Platform Class field. This means that each platform class increments this field autonomously. Software referencing this table should interpret the Platform Class field prior to interpreting this Revision field.
Checksum	1	9	Entire table must sum to zero.
OEMID	6	10	OEM ID. Per ACPI specification. An OEM-supplied string that identifies the OEM.
OEM Table ID	8	16	For the TPM Interface Table, the table ID is the manufacturer model ID (assigned by the OEM identified by "OEM ID").
OEM Revision	4	24	OEM revision of TPM Interface Table for the given OEM Table ID. Per ACPI, this is "An OEM-supplied revision number. Larger numbers are assumed to be newer revisions."
Creator ID	4	28	Vendor ID of the utility that created the table. For the tables containing Definition Blocks, this is the ID of the ASL Compiler.

Field	Byte Length	Byte Offset	Description
Creator Revision	4	32	Revision of the utility that created the table. For the tables containing Definition Blocks, this is the revision of the ASL Compiler.
Platform Class	2	36	See section 7.1.1.
Log Area Minimum Length (LAML)	4	38	Identifies the minimum length (in bytes) of the system's pre- boot TCG event log area. Note : The "TCG PC Client Specific Implementation Specification for conventional BIOS" version 1.21 defines a minimum log size of 64KB.
Log Area Start Address (LASA)	8	42	Contains the 64-bit physical address of the start of the system's pre-boot TCG event log area, in QWORD format. Note : The log area ranges from address LASA to LASA+(LAML-1).

7.2 Server ACPI Table for TPM 1.2

7.2.1 Server Common Header Values

These are the specific values to be used in the server platform version of the ACPI table for TPM 1.2.

Table 3: Defined values for Server ACPI table for TPM 1.2

Field	Value	Description
Length	100	Size of the table
Revision 2		Revision for Server Platform Class
Platform Class	1	Server Platform Class

7.2.2 ACPI Table Layout

Table 4: TCG Hardware Interface Description Table Format for TPM 1.2 Servers

Field	Byte Length	Byte Offset	Description
Header			
Signature	4	0	'TCPA'. Signature for the TCG Hardware Interface Table.
Length	4	4	See Section 7.2.1. The length of this table starting from the Signature field up to and including the PCI Function Number field. It does not include the size of the area storing events or other data that is referenced or pointed to by any of these fields.
Revision	1 8		See Section 7.2.1. Revision of this table including the data and structures referenced by it. E.g., if the event structures with the area referenced by LASA change, this revision shall be incremented.
			Note: The purview of this revision is within platform class as indicated by the Platform Class field. This means that each platform class increments this field autonomously. Software referencing this table should interpret the Platform Class field prior to interpreting this Revision field.
Checksum	1	9	Entire table must sum to zero.
OEMID	6	10	OEM ID. Per ACPI specification. An OEM-supplied string that identifies the OEM.

TCG Public Review Copyright © TCG 2017

Field	Byte Length	Byte Offset	Description
OEM Table ID	8	16	For the TPM Interface Table, the table ID is the manufacturer model ID (assigned by the OEM identified by "OEM ID").
OEM Revision	4	24	OEM revision of TPM Interface Table for the given OEM Table ID. Per ACPI, this is "An OEM-supplied revision number. Larger numbers are assumed to be newer revisions."
Creator ID	4	28	Vendor ID of the utility that created the table. For the tables containing Definition Blocks, this is the ID of the ASL Compiler.
Creator Revision	4	32	Revision of the utility that created the table. For the tables containing Definition Blocks, this is the revision of the ASL Compiler.
Platform Class	2	36	See Section 7.2.1.
Reserved	2	38	0 Note: This creates natural alignment for the fields that follow.
Log Area Minimum Length (LAML)	8	40	Identifies the minimum length (in bytes) of the system's pre- boot TCG event log area.
Log Area Start Address (LASA)	8	48	Contains the 64-bit physical address of the start of the system's pre-boot TCG event log area, in QWORD format. Note : The log area ranges from address LASA to LASA+(LAML-1).
Specification Revision	2	56	Identifies the TCG specification revision, in BCD format, to which the interface was designed. The first byte holds the most significant digits, while second byte holds the least significant digits of the revision, e.g. a value of 01 02 ₁₆ indicates the interface is compatible with TCG specification v1.2.
Device Flags	1	58	See Table 5
Interrupt Flags	1	59	See Table 6
GPE	1	60	The bit assignment of the SCI within the GPEx_STS register of a GPE described in the FADT that the interface triggers. Note: This field is valid only if Bit[2] of the Interrupt Flags field is set.)
Reserved	3	61	0
Global System Interrupt	4	64	The I/O APIC or I/O SAPIC Global System Interrupt used by the interface.
			Note: This field is valid only if Bit[3] of the Interrupt Flags field is set.
Base Address	12	68	The base address of the hardware register set described using the GAS. The Address_Space_ID field in the GAS can only have the values of 0 (System Memory) and 1 (System IO). All other values are not permitted. This address must be the Host Side address in the case of MMIO, and it must be the Host Side IO port address in the case of IO Port.
Reserved	4	80	Set to 0. This is to naturally align the data fields that follow.
Configuration Address	12	84	The configuration address of the TPM hardware device described using the GAS. The Address_Space_ID field in the GAS can only have the values of 0 (System Memory) and 1 (System IO). All other values are not permitted. This is only valid if Bit[2] of the Device Flags field is set. This address must be the Host Side address in the case of MMIO, and it must be the Host Side IO port address in the case of IO Port.
PCI Segment Group Number	1	96	PCI Segment Group Number, if the TPM device is a PCI device

Field	Byte Length	Byte Offset	Description
PCI Bus Number	1	97	PCI Bus Number, if the TPM device is a PCI device
PCI Device Number	1	98	Bit 4:0 – PCI Device Number: The PCI device number if the TPM device is a PCI device. Bit 7:5 – Reserved
PCI Function Number	1	99	Bit 2:0 – PCI Function Number: The PCI function number if the TPM device is a PCI device. Bit 7:3 – Reserved

7.2.3 Device Flags

Table 5: Bit layout of Device Flags

Bit	Description
73	Reserved
	TPM configuration address valid
2	0 = TPM configuration address is invalid
	1 = TPM configuration address is valid
	TPM Bus is PNP
1	0 = FALSE (the TPM address and interrupt must not be changed)
	1 = TRUE (the TPM address and interrupt may be changed by PNP OS code)
	PCI Device Flag. For PCI TCG devices, this bit is set.
0	0 = non-PCI device (The PCI Segment Group, Bus, Device and Function Number fields combined
Ű	correspond to the ACPI_UID value of the device whose _HID or _CID contains a TPM plug and play ID.)
	1 = PCI Device

7.2.4 Interrupt Flags

Table 6: Bit layout of Interrupt Flags

Bit	Description
74	Reserved
	I/O APIC/SAPIC interrupt (Global System Interrupt)
3	0 = not supported
	1 = supported
	SCI triggered through GPE
2	0 = not supported
	1 = supported
	Interrupt Polarity,
1	0 = Active-High: This interrupt is sampled when the signal is high, or true.
I	1 = Active-Low: This interrupt is sampled when the signal is low, or false.
	Note: PCI devices are always active low, so this bit is set to 1 for PCI devices.
	Interrupt Mode,
0	0 = Level-Triggered: This interrupt is triggered in response to the signal being in either a high or low state.
	1 = Edge-Triggered: This interrupt is triggered in response to a change in signal state, either high to low or low to high.
	Note: PCI devices are always level triggered, so this bit is set to 0 for PCI devices.

7.3 ACPI Table for TPM 2.0

This is the definition for the ACPI table for TPM 2.0.

Field	Byte Length	Byte Offset	Description	
Header				
Signature	4	0	'TPM2'. Signature for the TCG Hardware Interface Table.	
Length	4	4	The length of this table starting from the Signature field up to and including the Start Method specific parameters field. (52 + size of Start Method specific parameters) If the table contains LAML and LASA field, Length is 76.	
Revision	1	8	4. The current revision of this table.	
Checksum	1	9	Entire table must sum to zero.	
OEMID	6	10	OEM ID. Per ACPI specification. An OEM-supplied string that identifies the OEM.	
OEM Table ID	8	16	For the TPM Interface Table, the table ID is the manufacturer model ID (assigned by the OEM identified by "OEM ID").	
OEM Revision	4	24	OEM revision of TPM Interface Table for the given OEM Table ID. Per ACPI, this is "An OEM-supplied revision number. Larger numbers are assumed to be newer revisions."	
Creator ID	4	28	Vendor ID of the utility that created the table. For the tables containing Definition Blocks, this is the ID of the ASL Compiler.	
Creator Revision	4	32	Revision of the utility that created the table. For the tables containing Definition Blocks, this is the revision of the ASL Compiler.	
Platform Class	2	36	0 for client platforms. 1 for server platforms.	
Reserved	2	38	0	
Address of Control Area	8	40	Physical address of the Control Area. The Control Area contains status registers and the location of the memory buffers for communicating with the device. The area may be in either TPM 2.0 device memory or in memory reserved by the system during boot. Interfaces that do not require the Control Area set this value to zero.	
Start Method	4	48	The Start Method selector determines which mechanism the device driver uses to notify the TPM 2.0 device that a command is available for processing. This field may contain one of the values specified in Table 8.	
Start Method Specific Parameters	Variable (up to 12)	52	The content of the Start Method specific parameters is determined by the Start Method used by the system's TPM device interface. This field contains values that may be used to initiate command processing. If the Start Method value is 2, then this field is at least four bytes in size and the first four bytes must be all zero. If the Start Method value is 11 then this field is 12 bytes in size and is described in Table 9. If LAML and LASA are present, then this field is 12 bytes in size.	

Table	7:	TCG	Hardware	Interface	Description	Table	Format	for TPM	2.0

Field	Byte Length	Byte Offset	Description
Log Area Minimum Length (LAML)	4	64	Optional. Identifies the minimum length (in bytes) of the system's pre- boot TCG event log area. Note : The "TCG PC Client Specific Implementation Specification for conventional BIOS" version 1.21 defines a minimum log size of 64KB.
Log Area Start Address (LASA)	8	68	Optional. Contains the 64-bit physical address of the start of the system's pre-boot TCG event log area, in QWORD format. Note: The log area ranges from address LASA to LASA+(LAML-1). Note: The format of the TCG event log area is defined in the "PC Client Platform Firmware Profile Specification", Section 9. The crypto agile log format as defined by the "PC Client Platform Firmware Profile Specification" should be used.

Table 8: Start Method values for ACPI table for TPM 2.0

Value	Description
0	Not allowed (indicates value has not been set).
1	Reserved for legacy use (vendor specific).
2	Uses the ACPI Start method.
3 – 5	Reserved for legacy use (vendor specific).
6	Reserved for the Memory mapped I/O Interface (TIS 1.2+Cancel).
7	Uses the Command Response Buffer Interface.
8	Uses the Command Response Buffer Interface with the ACPI Start Method.
9 – 10	Reserved for legacy use (vendor specific)
11	Uses the Command Response Buffer Interface with ARM Secure Monitor Call (SMC)
12+	Reserved for future use

7.3.1 Start Method Specific Parameters for ARM SMC Start Method (11)

The following table describes the definition of the Start Method specific parameters when the ACPI Start Method value is 11.

Field	Byte Length	Byte Offset	Description
Interrupt	4	52 ¹	Global System Interrupt Vector of the TPM interrupt. Must be zero if interrupt is not supported

Table 9: Start Method Specific Parameters for ARM SMC

¹ Byte Offset of Start Method Specific Parameters starts from 52 per **Error! Reference** source not found..

Field	Byte Length	Byte Offset	Description
Flags	1	56	Bits 1:7 – Reserved for future use Bit 0 – Interrupt support 1: Interrupt is supported ² 0: No Interrupt, (software must poll CRB status)
Operation Flags	1	57	Bits 1:7 – Reserved for future use Bit 0 – TPM Idle Support 1: CRB interface state transitions include "Idle", "Ready", "Reception", "Execution", and "Completion" 0: CRB interface state transitions only include "Ready" and "Execution" states
Reserved	2	58	0
SMC Function ID	4	60	This field provides the SMC call function ID that will invoke the TPM start method.

² Interrupt must always be edge when using ARM SMC

8 ACPI Device

Devices are not required to be exposed in ACPI namespace if the device exists on a bus that is enumerable by the Operating System, or on a bus which is plug-n-play capable.

A TCG platform class-specific ACPI Table may provide a mechanism that can be used before the ability to execute ACPI control methods in the OS is available. The Server ACPI Table in section 2.2 of this specification is one example of such a table. This table is not, however, intrinsically supported in the OSPM as a way of discovering and reporting system resources. Therefore, it is recommended that non-PCI TCG Hardware on the platform be described in the ACPI name space. This makes it possible for the OSPM to enumerate the TCG Hardware as a device. In addition, the ACPI name space description is more flexible and friendly in hot-plug scenarios.

Note that to be ACPI compatible, the fixed resources for TCG Hardware must still be accounted for in accordance with the ACPI specification. If the device is not formally described in the ACPI Name Space, its resources must be described as fixed system resources or the resources appended to some other fixed resource system device in order to ensure that the OSPM does not attempt to allocate those resources to some other device.

To formally describe the TCG Hardware System Interface in ACPI Name Space, a TCG hardware device is created using the named device object. Table 10 is a non-exhaustive list of ACPI control methods that may be used in a TCG hardware device object, along with a recommended support level for each method.

A TCG platform may provide an ACPI device object representing the TPM in the ACPI namespace, if the bus where the TPM is located is not PNP capable or the bus is not exposed to the OS for PNP operations.

It is recommended that TPM 2.0 device object ACPI table appears under the DSDT table in the ACPI namespace. The TPM 2.0 device object should be located under the system bus.

Table 10: TCG Hardware Device Object Control Methods

Object	Description	Support Level
_ADR	Named object that evaluates to the interface's address on its parent busADR is a standard device configuration control method defined in the ACPI Specification.	Required only for devices on a bus that has standard enumeration mechanism.
_HID	Named object that provides the interface's Plug and Play identifier. This value may be TPM vendor specificHID is a standard device configuration control method defined in the ACPI Specification.	Required only for devices that do not have standard enumeration mechanism.
_CID	Named object (or list of named objects) that provide alternative Plug and Play identifiers. Depending on the platform, the _CID can be used to identify a compatible class driver for the TPM deviceCID is a standard device configuration control method defined in the ACPI Specification.	Optional
_STR	Named object that evaluates to a Unicode string that may be used by an OS to provide information to an end user describing the deviceSTR is a standard device configuration control method defined in the ACPI Specification.	Optional
_UID	Named object that specifies a device's unique persistent ID, or a control method that generates itUID is a standard device configuration control method defined in the ACPI Specification.	Optional
_CRS	Named object that returns the TPM interface's current resource settings. Security hardware Interfaces are considered static resources; hence only return their defined resources. The address region definition is interface type/subtype dependentCRS is a standard device configuration control method defined in the ACPI Specification.	Required
_STA	Object that returns the status of the device: enabled, disabled or removed, as defined in the ACPI Specification. If this method is not present, the device is assumed to be enabled.	Recommended
_DSM	Device Specific Method	Optional
	Function 0 – standard query function	
	Function 1 – TCG Hardware Information	
	Arguments:	
	Arg0 (Buffer): UUID = {CF8E16A5-C1E8-4e25-B712-4F54A96702C8}	
	Arg1 (Integer): Revision ID = 1 Arg2 (Integer): Exection Index. 4	
	Arg2 (Integer): Function Index = 1	
	Arg3 (Package): Arguments = Empty Package	
	Type: Package	
	Package item 1:	
	Type: Integer	
	Purpose: status of operation	
	Description:	
	0: Failure	
	1: Success	
	Package item 2:	
	Type: Package	
	Purpose: ICG Revision implemented in security hardware	
	Package item 1:	
	i ype: integer Description: (BCD format) – most significant digits of TCC version	
	Package Item 2.	
	Type: Integer	
	Description: (BCD format) – least significant digits of TCG version	
	For example: a value of 0x0110 indicates the interface is compatible with TCG specification v1.1.	

Object	Description	Support Level
_GPE	Named object that evaluates to either an integer or a package. If _GPE evaluates to an integer, the value is the bit assignment of the SCI within the GPEx_STS register of a GPE block described in the FADT that the Security hardware device will trigger. If _GPE evaluates to a package, then that package contains two elements. The first is an object reference to the GPE Block device that contains the GPE register that will be triggered by the interface. The second element is numeric (integer) that specifies the bit assignment of the SCI within the GPEx_STS register of the GPE Block device referenced by the first element in the package. Note: This object is only provided if the interface supports a GPE.	Required if interrupt through GPE is supported

8.1 Optional Start Method for TPM 2.0 devices

Some platforms may implement an optional ACPI Start Method to permit the OS to request the firmware to execute or cancel a TPM 2.0 command. The use of the ACPI Start method is determined by the StartMethod field of the static TPM2 ACPI table (see Section 7.2.3.) If the StartMethod field of the static ACPI table indicates the use of this method, the ACPI Start Method shall be implemented. The ACPI functions defined herein shall reside in the _DSM control method object.

The _DSM method defined herein shall be implemented as follows:

Function 0 – standard query function

Function 1 – ACPI Start Method

Arguments:

Arg0 (Buffer): UUID = 6bbf6cab-5463-4714-b7cd-f0203c0368d4

Arg1 (Integer): Revision ID = 0

Arg2 (Integer): Function Index = 1

Arg3 (Package): Arguments = Empty Package

Return Value:

Type: Integer

Description of the Return Value:

0: Success

1: General Failure

Functional Behavior:

This function tells the system to review the fields in the TPM 2.0 device control area and take the appropriate action, such as, but not limited to, execute or cancel a TPM 2.0 command.

The function is non-blocking. The call will return immediately. When Return Value 0 is returned, the TPM inspected the control area and will take appropriate action. For instance, if a command has been submitted and *Start* is SET, the command was accepted and will be executed by the TPM. Whenever possible the system should return a TPM response instead of a General Failure from this call. For example, if a command cannot be processed when the method is called, a Response buffer of TPM2_RC_Retry could be written to the TPM's response area and the *Start* field in the Control Area could be CLEARed. If the command was cancelled because the *Cancel* field was set, this

method may write a TPM2_RC_Cancelled return code in the Response buffer, clear the *Start* field in the Control Area and return a value of 0. Alternatively, if the *Cancel* field is set the method may return a value of 0 and the TPM 2.0 device may later complete or cancel the command per the requirements for cancelling a command.

When 1 is returned, the firmware is unable to read or act upon the request. Other than the return value, the request is equivalent to a NO-OP. Examples are (a) a bad OS driver requests execution of additional commands before a prior command completed, (b) the control area is not in physical memory, or (c) the command or response physical addresses do not exist. A return value of 1 may cause software to stop using the TPM 2.0 device until the next full system boot (this excludes hibernation/resume cycles).